

Certificate

Issue Date: July 15, 2021
Ref. Report No. ISL-21LR190ICES003

Product Name : Bluetooth 5.1 Module
Model(s) : BC40C; BC40M; BC40P
Brand : Fanstel
Applicant : Fanstel Corporation, Taipei
Address : 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-Chih, New Taipei City 221 Taiwan

We, **International Standards Laboratory Corp.**, hereby certify that:

The sample ISL received which bearing the trade name and model specified above has shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified. (refer to Test Report if any modifications were made for compliance). And Our laboratories is the accredited laboratories and are approved according to ISO/IEC 17025.

Standards:

Industry Canada Interference-Causing Equipment Standard ICES-003 Issue 7: 2020
Class B

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The determination of the test results is determined by customer agreement, regulations or standard document specifications.

The Laboratory evaluates measurement inaccuracies based on regulatory or standard document specifications and is listed in the report for reference. The quantitative project part judges the conformity of the test results based on the evaluation results of the standard cited uncertainty, and the qualitative project does not temporarily evaluate the measurement uncertainty.



Angus Chu / Sr. Manager

International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

TEST REPORT

Of

Industry Canada Interference-Causing Equipment Standard ICES-003 Class B

Product : **Bluetooth 5.1 Module**
Model(s): **BC40C; BC40M; BC40P**
Brand: **Fanstel**
Applicant: **Fanstel Corporation, Taipei**
Address: **10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-Chih, New Taipei City 221 Taiwan**

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

Report No.: **ISL-21LR190ICES003**
Issue Date : **July 15, 2021**





Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein. The uncertainty of the measurement does not include in consideration of the test result unless the customer required the determination of uncertainty via the agreement, regulation or standard document specification. This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

Contents of Report

1.	General	1
1.1	Certification of Accuracy of Test Data	1
1.2	Description of EUT	2
1.3	Configuration of Tested System	4
2.	Power Line Conducted Emissions.....	5
2.1	Test Setup and Procedure	5
2.2	<i>Conduction Test Data: Configuration 1</i>	7
2.3	Test Setup Photo.....	9
3.	Radiated Emissions	10
3.1	Test Setup and Procedure	10
3.2	<i>Radiation Test Data: Configuration 1</i>	14
3.3	Test Setup Photo.....	18
4.	Appendix	20
4.1	Appendix A: Labelling and user manual requirements	20
4.2	Appendix B: Test Equipment	21
4.3	Appendix C: Uncertainty of Measurement.....	22
4.4	Appendix D: Photographs of EUT	23

1. General

1.1 Certification of Accuracy of Test Data

Standards:	Industry Canada Interference-Causing Equipment Standard ICES-003 Issue 7: 2020 Class B
Equipment Tested:	Bluetooth 5.1 Module
Model:	BC40C; BC40M; BC40P
Brand:	Fanstel
Applicant:	Fanstel Corporation, Taipei
Sample received Date:	June 28, 2021
Final test Date:	refer to the date of test data
Test Site:	Chamber 19; Conduction 04; Immunity02
Test Distance:	3m; 3m (1GHz-18GHz)
Temperature:	refer to each site test data
Humidity:	refer to each site test data
Input power:	Conduction input power: AC 120 V / 60 Hz Radiation input power: AC 120 V / 60 Hz
Test Result:	PASS
Report Engineer:	Gigi Yeh
Test Engineer:	 Jason Chao
Approved By:	 Jerry Liu / Assistant Manager

1.2 Description of EUT

EUT

General:

Product Name	Bluetooth 5.1 Module
Brand Name	Fanstel
Model Name	BC40C; BC40M; BC40P
Model Difference	Antenna difference
Power Supply	5Vdc from USB (JIG)
USB port	one (JIG)

Model Summaries:

module	BC40C	BC40M	BC40P
SoC	nRF5340 CLAA	nRF5340 CLAA	nRF5340 CLAA
Size	8.4x11.5x1.5 mm	8.4(10.1)x12.7x1.5mm	8.4x9x1.5mm
32 MHz and 32.768 kHz crystals	Integrated	Integrated	Integrated
DC converter inductors, VDD,VDDH	Integrated	Integrated	Integrated
BT Antenna	Chip	PCB trace	Pads for external
Max TX			
Operating temp.	-40°C to +105°C	-40°C to +105°C	-40°C to +105°C
Availability	Sample 05/2021	Sample 05/2021	Sample 06/2021

Description of test modes

Test Plan

Applicable standard		ICES-003		
Test Configuration		Config 1	Config 2	Config 3
		EUT + Smart mobile phone	EUT + Smart mobile phone	EUT + Smart mobile phone
Operation mode		BT link(BC40M)	BT link(BC40P) Antenna:Ant020	BT link(BC40C)
No.	Description			
1	Radiated emission(30M~1GHz)(above 1GHz)	Measured	Pretest	Pretest
3	Conducted emission (AC Power)	Measured	N/A	N/A

Note 1: the test plan was accept by the applicant

1.3 Configuration of Tested System

Fig. 1-1 Configuration

Config 1




Table 1-1 Support Equipment Used in Tested System

Item	Equipment	Mrf/Brand	Model name	Series No	Data Cable	Power Cable
1	adaptor	Apple	A1385	N/A	N/A	Shielded /1m
2	Smart mobile phone	hTC	PL99110	N/A	N/A	N/A

I/O Cable Condition of EUT and Support Units

Description	Path	Cable Length	Cable Type	Connector Type
USB power cable	Adaptor USB port to JIG micro USB port	1m	Shielded	Metal Head


Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

2. Power Line Conducted Emissions

2.1 Test Setup and Procedure

2.1.1 Test Setup



2.1.2 Test Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, hot and neutral, were measured. All of the interface cables were manipulated according to ANSI C63.4 requirements.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

2.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150kHz~30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9kHz

2.1.4 Limit


Conducted emissions limits of Class A equipment. (AC mains power terminals):

Frequency range (MHz)	Quasi-peak (dB μ V)	Average (dB μ V)
0.15-0.50	79	66
0.50-5.0	73	60
5.0-30	73	60
Note: The more stringent limit applies at transition frequencies.		

Conducted emissions limits of Class B equipment. (AC mains power terminals):

Frequency range (MHz)	Quasi-peak (dB μ V)	Average (dB μ V)
0.15-0.50	66 to 56*	56-46*
0.50-5.0	56	46
5.0-30	60	50
*The limit level in dB μ V decreases linearly with the logarithm of frequency. Note: The more stringent limit applies at transition frequencies.		

2.2 Conduction Test Data: Configuration 1 -Line



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.474	9.11	-0.96	9.70	18.81	56.44	-37.63	8.74	46.44	-37.70
2	0.662	10.34	0.13	9.71	20.05	56.00	-35.95	9.84	46.00	-36.16
3	0.702	11.70	3.36	9.70	21.40	56.00	-34.60	13.06	46.00	-32.94
4	0.774	14.49	6.97	9.71	24.20	56.00	-31.80	16.68	46.00	-29.32
5	4.150	6.04	2.08	9.80	15.84	56.00	-40.16	11.88	46.00	-34.12
6	5.098	6.63	2.37	9.82	16.45	60.00	-43.55	12.19	50.00	-37.81

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.


- Neutral



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888

Conducted Emission Measurement
Date: 2021/7/5

operator: Jason
Temperature: 26 °C
Humidity: 54 %



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.162	15.25	0.59	9.71	24.96	65.36	-40.40	10.30	55.36	-45.06
2	0.470	9.90	-0.90	9.70	19.60	56.51	-36.91	8.80	46.51	-37.71
3	0.510	9.41	0.23	9.70	19.11	56.00	-36.89	9.93	46.00	-36.07
4	0.698	12.33	2.69	9.70	22.03	56.00	-33.97	12.39	46.00	-33.61
5	0.790	13.61	4.79	9.71	23.32	56.00	-32.68	14.50	46.00	-31.50
6	2.238	3.89	-0.65	9.76	13.65	56.00	-42.35	9.11	46.00	-36.89

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.


If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.3 Test Setup Photo

Front View




Back View



3. Radiated Emissions

3.1 Test Setup and Procedure

3.1.1 Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.
 1GHz~18GHz

Frequency GHz	E-plane	H-plane	$\theta_{3dB}(\text{min})$	d= 3 m
				w (m)
1	88°	147°	88°	5.79
2	68°	119°	68°	4.04
3	73°	92°	73°	4.44
4	70°	89°	70°	4.20
5	55°	60°	55°	3.12
6	63°	62°	62°	3.60
7	48°	49°	48°	2.67
8	39°	46°	39°	2.12
9	32°	42°	32°	1.72
10	30°	39°	30°	1.61
11	32°	35°	32°	1.72
12	35°	32°	35°	1.89
13	34°	31°	31°	1.66
14	32°	27°	27°	1.44
15	36°	26°	26°	1.39
16	40°	28°	28°	1.50
17	43°	26°	26°	1.39
18	41°	22°	22°	1.17

18 GHz~26.5 GHz

Frequency GHz	E-plane	H-plane	$\theta_{3dB}(\text{min})$	d= 1 m	d= 3 m
				w (m)	w (m)
18	11.4°	12.7°	11.4°	0.199	0.598
19	10.9°	12.4°	10.9°	0.190	0.572
20	10.8°	12.4°	10.8°	0.189	0.567
21	9.8°	12°	9.8°	0.171	0.514
22	9.7°	11°	9.7°	0.169	0.509
23	10°	11.8°	10°	0.174	0.524
24	9°	11°	9°	0.157	0.472
25	10°	12.3°	10°	0.174	0.524
26	9.9°	11.1°	9.9°	0.173	0.519
26.5	9.4°	11.3°	9.4°	0.164	0.493

26 GHz~40 GHz

Frequency GHz	E-plane	H-plane	$\theta_{3dB}(\text{min})$	d= 1 m	d= 3 m
				w (m)	w (m)
26	12°	12.2°	12°	0.210	0.631
27	13°	10.5°	10.5°	0.184	0.551
28	13.2°	12.3°	12.3°	0.216	0.647
29	11.5°	12.8°	11.5°	0.201	0.604
30	12°	8°	8°	0.140	0.420
31	11.5°	10.1°	10.1°	0.177	0.530
32	11.8°	10°	10°	0.175	0.525
33	11.8°	9.5°	9.5°	0.166	0.499
34	11.6°	10°	10°	0.175	0.525

35	10.9°	9.8°	9.8°	0.171	0.514
36	11.8°	8.6°	8.6°	0.150	0.451
37	12.9°	10.5°	10.5°	0.184	0.551
38	12°	10.3°	10.3°	0.180	0.541
39	11.8°	9.8°	9.8°	0.171	0.514
40	12.5°	11.2°	11.2°	0.196	0.588

3.1.2 Test Procedure

The radiated emissions test will then be repeated on the chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 3 meter chamber. Desktop EUT are set up on a wooden stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 40 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the antenna in the cone of radiation from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response. At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to ANSI C63.4 requirements.

The highest internal source of the EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes. If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 40 GHz, whichever is less.

3.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1000MHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

3.1.4 Limit

Radiated emissions limits of Class_A equipment. (30 MHz to 1 GHz)

Frequency range (MHz)	at 3 m distance Quasi-peak (dB μ V/m)
30-88	50.0
88-216	54.0
216-230	56.9
230-960	57.0
960-1000	60.0

Note: The more stringent limit applies at transition frequencies.

Radiated emission limits of Class_A equipment at 3 m distance (at and above 1 GHz)

Frequency range (GHz)	Average dB(μ V/m)	Peak dB(μ V/m)
1 – 40G	60	80

Note 1: Limit is measurement distance using an inverse linear distance extrapolation factor (20dB/decade).

Radiated emissions limits of Class_B equipment. (30 MHz to 1 GHz)

Frequency range (MHz)	at 3 m distance Quasi-peak (dB μ V/m)
30-88	40.0
88-216	43.5
216-230	46.0
230-960	47.0
960-1000	54.0

Note: The more stringent limit applies at transition frequencies.

Radiated emission limits of Class_B equipment at 3 m distance (at and above 1 GHz)

Frequency range (GHz)	Average dB(μ V/m)	Peak dB(μ V/m)
1 – 40G	54	74


Note 1: Limit is measurement distance using an inverse linear distance extrapolation factor (20dB/decade).

3.2 Radiation Test Data: Configuration 1

- Radiated Emissions (Horizontal)



International Standard Laboratory Corp.
 Company Address: No. 120, Lane 180, Hsin Ho Rd.
 Lung-Tan Dist., Tao Yuan City 325, Taiwan
 Tel: (03) 4071718 ; Fax: (03) 4071738
 Web: www.isl.com.tw



Condition: ICES-003 CLASS B 3M 3m HORIZONTAL
 Site : Chamber 19

Operator : Jason

	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	53.28	29.05	-6.32	22.73	40.00	-17.27	Peak	HORIZONTAL
2	166.77	33.20	-5.69	27.51	43.50	-15.99	Peak	HORIZONTAL
3	757.50	30.36	3.85	34.21	47.00	-12.79	Peak	HORIZONTAL
4	818.61	30.03	4.45	34.48	47.00	-12.52	Peak	HORIZONTAL
5	896.21	30.11	5.48	35.59	47.00	-11.41	Peak	HORIZONTAL
6	925.31	29.90	6.32	36.22	47.00	-10.78	Peak	HORIZONTAL

- 1 -

* Note:

Margin = Emission - Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Tel: (03) 4071718 ; Fax: (03) 4071738
Web: www.isl.com.tw



Condition: FCC CLASS B 3M PK 3m HORIZONTAL
Site : Chamber 19

Operator : Jason

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2575.00	49.99	-11.48	38.51	74.00	-35.49	Peak	HORIZONTAL
2	3125.00	49.22	-10.31	38.91	74.00	-35.09	Peak	HORIZONTAL
3	3750.00	48.32	-9.16	39.16	74.00	-34.84	Peak	HORIZONTAL
4	4250.00	48.07	-8.57	39.50	74.00	-34.50	Peak	HORIZONTAL
5	4825.00	48.07	-7.30	40.77	74.00	-33.23	Peak	HORIZONTAL
6	6850.00	46.71	-3.56	43.15	74.00	-30.85	Peak	HORIZONTAL

- 1 -

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit


Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

-Radiated Emissions (Vertical)



International Standard Laboratory Corp.
 Company Address: No. 120, Lane 180, Hsin Ho Rd.
 Lung-Tan Dist., Tao Yuan City 325, Taiwan
 Tel: (03) 4071718 ; Fax: (03) 4071738
 Web: www.isl.com.tw



Condition: ICES-003 CLASS B 3M 3m VERTICAL
 Site : Chamber 19

Operator : Jason

	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	57.16	31.54	-6.62	24.92	40.00	-15.08	Peak	VERTICAL
2	170.65	35.02	-5.83	29.19	43.50	-14.31	Peak	VERTICAL
3	621.70	30.99	1.27	32.26	47.00	-14.74	Peak	VERTICAL
4	773.99	30.51	4.00	34.51	47.00	-12.49	Peak	VERTICAL
5	834.13	30.29	4.68	34.97	47.00	-12.03	Peak	VERTICAL
6	932.10	30.32	6.44	36.76	47.00	-10.24	Peak	VERTICAL

- 1 -

* Note:

Margin = Emission - Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Tel: (03) 4071718 ; Fax: (03) 4071738
Web: www.isl.com.tw



Condition: FCC CLASS B 3M PK 3m VERTICAL
Site : Chamber 19

Operator : Jason

	Freq	Read		Limit	Over		
	MHz	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Pol/Phase
1	2575.00	50.13	-11.48	38.65	74.00	-35.35	Peak
2	3025.00	49.09	-10.64	38.45	74.00	-35.55	Peak
3	3725.00	48.88	-9.23	39.65	74.00	-34.35	Peak
4	4600.00	47.32	-7.61	39.71	74.00	-34.29	Peak
5	5625.00	47.21	-5.78	41.43	74.00	-32.57	Peak
6	6525.00	46.76	-3.77	42.99	74.00	-31.01	Peak

- 1 -

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters


Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

3.3 Test Setup Photo


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)



Back View (above 1GHz)



4. Appendix

4.1 Appendix A: Labelling and user manual requirements

The requirements specified in ICES-Gen shall apply. An example ISED compliance label, to be placed on each unit of an equipment model (or in the user manual, if allowed), is given below:

CAN ICES-003(*) / NMB-003(*)

* Insert either “A” or “B”, but not both, to identify the applicable Class of the device used for compliance verification.

The above label is only an example. The specific format is left to the manufacturer to decide, as long as the label includes the required information, in accordance with ICES-Gen.

4.2 Appendix B: Test Equipment

4.2.1 Test Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 04	LISN 18	ROHDE & SCHWARZ	ENV216	101424	07/01/2020	07/01/2021
Conduction 04	LISN 03	R&S	ESH3-Z5	828874/010	11/05/2020	11/05/2021
Conduction 04	ISN T8 07	Teseq GmbH	ISN T800	30834	09/03/2020	09/03/2021
Conduction 04	ISN T4 06	Teseq GmbH	ISN T400A	28574	10/15/2020	10/15/2021
Conduction 04	Chamber05 -1 Cable	WOKEN	CFD 300-NL	Chamber05 -1 Cable	08/22/2020	08/22/2021
Conduction 04	EMI Receiver 18	ROHDE&SCHWARZ	ESCI	101392	06/08/2021	06/08/2022

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Chamber 19	Spectrum analyzer	R&S	FSV40	101919	08/13/2020	08/13/2021
Chamber 19	EMI Receiver	R&S	ESR3	102461	05/05/2021	05/05/2022
Chamber 19	Loop Antenna	EM	EM-6879	271	05/21/2021	05/21/2022
Chamber 19	Bilog Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168 w 6dB Att.	9168-736	02/22/2021	02/22/2022
Chamber 19	Horn antenna (1GHz-18GHz)	ETS LINDGREN	3117	00218718	09/25/2020	09/25/2021
Chamber 19	Horn antenna (18GHz-26GHz)	Com-power	AH-826	081001	11/23/2020	11/23/2021
Chamber 19	Horn antenna (26GHz-40GHz)	Com-power	AH-640	100A	03/11/2021	03/11/2022
Chamber 19	Preamplifier (9kHz-1GHz)	HP	8447F	3113A04621	06/19/2021	06/19/2022
Chamber 19	Preamplifier (1GHz-26GHz)	EM	EM01M26G	060681	05/07/2021	05/07/2022
Chamber 19	Preamplifier (26GHz-40GHz)	MITEQ	JS4-26004000-27-5A	818471	05/07/2021	05/07/2022
Chamber 19	RF Cable (9kHz-18GHz)	HUBER SUHNER	Sucoflex 104A & 18GHz SMA(M)-SMA(M)-10M	MY817/4A & 20200525	12/25/2020	12/25/2021
Chamber 19	RF Cable (18GHz-40GHz)	HUBER SUHNER	Sucoflex 102	27963/2&3742 1/2	11/19/2020	11/19/2021
Chamber 19	Signal Generator	Anritsu	MG3692A	20311	01/03/2021	01/03/2022
Chamber 19	Test Software	Audix	E3 Ver:6.12023	N/A	N/A	N/A

4.2.2 Software for Controlling Spectrum/Receiver and Calculating Test Data

Site	Filename	Version	Issue Date
Conduction	EZ EMC	ISL-03A2	3/6/2013

4.3 Appendix C: Uncertainty of Measurement

The laboratory measurement uncertainty accordance with refers to CISPR 16-4-2. If U_{lab} is less than or equal to U_{Cispr} in Table 1, then the test report may either state the value of U_{lab} or state that U_{lab} is less than U_{Cispr} .

The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 04>

AMN: $\pm 2.90\text{dB}$

ISN T4: $\pm 3.05\text{dB}$

ISN T8: $\pm 3.05\text{dB}$

CVP: $\pm 3.62\text{dB}$

CP: $\pm 2.88\text{dB}$

<Chamber 19 (3M)>

30MHz~1000MHz: $\pm 4.22\text{ dB}$

1GHz~40GHz: $\pm 4.08\text{ dB}$

4.4 Appendix D: Photographs of EUT

Please refer to the File of **ISL-21LR190P**

--- END ---