

# **TEST REPORT**

of

## **Australian/New Zealand Standard AS/NZS 4268:2017**

**Product :** Bluetooth 5.2 Module

**Brand:** Fanstel

**Model:** BC805M

**Model Difference:** N/A

**Applicant:** Fanstel Corporation, Taipei

**Address:** 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,  
Hsi-Chih, New Taipei City 221 Taiwan

**Test Performed by:**  
**International Standards Laboratory Corp.**

<LT Lab.>

\*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997

\*Address:

No. 120, Lane 180, Hsin Ho Rd.,

Lung-Tan Dist., Tao Yuan City 325, Taiwan

\*Tel : 886-3-407-1718; Fax: 886-3-407-1738

**Report No.: ISL-20LR274ANZ**

**Issue Date : 2020/10/05**

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

The uncertainty of the measurement does not include in consideration of the test result unless the customer required the determination of uncertainty via the agreement, regulation or standard document specification.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

## VERIFICATION OF COMPLIANCE

**Applicant:** Fanstel Corporation, Taipei  
**Product Description:** Bluetooth 5.2 Module  
**Brand Name:** Fanstel  
**Model No.:** BC805M  
**Model Difference:** N/A  
**Date of test:** 2020/09/03 ~ 2020/09/30  
**Date of EUT Received:** 2020/09/03

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
AS/NZS 4268:2017, Row 59	Complied

### We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:

*Weitin Chen*

Date:

2020/10/05

*Weitin Chen / Senior Engineer*

Prepared By:

*Gigi yeh*

Date:

2020/10/05

*Gigi Yeh / Senior Engineer*

Approved By:

*Jerry Liu*

Date:

2020/10/05

*Jerry Liu / Technical Manager*

## Version

Version No.	Date	Description
00	2020/10/05	Initial creation of document

## Table of Contents

1	Description of Equipment Under Test (EUT) .....	5
2	Description of Test Modes and Test Condition .....	7
3	General Description of Apply Standards .....	8
4	Test Facility .....	8
5	Support Equipment .....	9
6	Maximum EIRP Measurement .....	10
7	Transmitter Spurious Emissions Measurement .....	12
8	Emission Bandwidth Measurement .....	15
9	Operating Frequencies Measurement .....	16
10	Receiver Emissions Measurement .....	18
11	Radiated Peak Power Spectral Density Measurement .....	21
	Photographs of Test Setup .....	22
	Photographs of EUT .....	24

## 1 Description of Equipment Under Test (EUT)

General:

Product Name:	Bluetooth 5.2 Module
Brand Name:	Fanstel
Model Name:	BC805M
Model Difference:	N/A
Type of Equipment:	Stand-alone equipment
Temperature Range:	-40°C to +85°C
Simultaneous transmissions:	Yes
Geo-location capability:	No
Power Supply	5Vdc by USB port

Bluetooth Version	BT 5.2
Frequency Range:	2402 – 2480MHz
Channel number:	40 channels
Modulation type:	Wide band Modulation
Transmit Power: (EIRP)	5.84 dBi
Dwell Time	N/A
Operating Mode	Point-to-Point
Adaptive/ Non-Adaptive	Non-Adaptive
LBT (Listen Before Talk)	Yes
	<input checked="" type="checkbox"/> Adaptive Frequency Hopping using LBT based DAA <input type="checkbox"/> Adaptive Frequency Hopping using other forms of DAA (non-LBT based) <input type="checkbox"/> Short Control Signaling Transmissions
Occupied Channel Bandwidth	Within 2400-2483.5MHz
Duty Cycle	N/A
Antenna Beam forming	No
Antenna Designation:	PCB Antenna: 0.14 dBi

This test report applies for Bluetooth BLE.

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 2 Description of Test Modes and Test Condition

The EUT has been tested under Operating and standby condition. And used to control the EUT for staying in continuous transmitting and receiving mode is programmed. Channel lower, mid and higher of Bluetooth BLE modes were chosen for testing.

### **Normal test conditions:**

Temperature : -20°C to 55°C

Relative humidity: 20 % to 75 %

5Vdc Voltage

### **Extreme Temperatures**

For test at extreme temperatures, measurements shall be in accordance with the procedures specified in section 5.3 of AS/NZS 4268 at upper value of +85 degree and at a lower value of -40 degree.

### **Extreme Test Source Voltages**

Low voltage is 4.5Vdc and 5.5Vdc for high voltage nominal voltage 5Vdc

### **3 General Description of Apply Standards**

The EUT According to the Specifications, it must comply with the requirements of the following standards:

AS/NZS 4268:2017, – Radio equipment and systems – Short range devices – Limits and methods of measurement.

Row 59: Digital modulation transmitters

### **4 Test Facility**

International Standards Laboratory Corp.

<LT Lab.>

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

A fully anechoic chamber was used for the radiated spurious emissions test.

TAF Accreditation Lab. Lab number: 0997



## 5 Support Equipment

Fig. 5-1 Configuration of Tested System



Table 5-1 Equipment Used in Tested System

Item	Equipment	Mrf/Brand	Model name	Series No	Data Cable	Power Cable
1	Notebook	Lenovo	X220i	N/A	N/A	Non-shielded
2	Test Kit	N/A	N/A	N/A	N/A	N/A

## 6 Maximum EIRP Measurement

### 6.1. Limit:

4W(36dBm) for Row 59

10W(20dBm) for Row 21


According to AS/NZS 4268:2017, Table 1, row 59: Digital modulation transmitters

According to AS/NZS 4268:2017, Table 1, row 21: All transmitters

### 6.2. Measurement Equipment Used:

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conducted	Power Meter	Anritsu	ML2495A	1116010	09/25/2020	09/25/2021
Conducted	Power Sensor	Anritsu	MA2411B	34NKF50	09/25/2020	09/25/2021
Conducted	Power Sensor	DARE	RPR3006W	13I00030SNO33	01/03/2020	01/03/2021
Conducted	Power Sensor	DARE	RPR3006W	13I00030SNO34	01/09/2020	01/09/2021
Conducted	Power Sensor	DARE	RPR3006W	14I00889SNO35	06/29/2020	06/29/2021
Conducted	Power Sensor	DARE	RPR3006W	14I00889SNO36	06/29/2020	06/29/2021
Conducted	Temperature Chamber	KSON	THS-B4H100	2287	03/11/2020	03/11/2021
Conducted	DC Power supply	ABM	8185D	N/A	01/03/2020	01/03/2021
Conducted	AC Power supply	EXTECH	CFC105W	NA	N/A	N/A
Conducted	Spectrum analyzer	Keysight	N9010A	MY56070257	09/23/2020	09/23/2021
Conducted	Spectrum analyzer	R&S	FSP40	100116	01/10/2020	01/10/2021
Conducted	Test Software	DARE	Radiation Ver:2013.1.23	NA	NA	NA
Conducted	Test Software	R&S	CMUGO Ver:2.0.0	N/A	N/A	N/A
Conducted	Radio Communication Analyzer	R&S	CMU200	111968	11/29/2019	11/29/2020
Conducted	Radio Communication Analyzer	R&S	CMW500	1201.002K50108793-JG	10/11/2019	10/11/2020
Conducted	BT Simulator	Agilent	N4010A	MY48100200	NA	NA
Conducted	GPS Simulator	Welnavigate	GS-50	701523	NA	NA

### 6.3. Test Setup:



### 6.4. Test Procedure:

Refer to ETSI EN 300 440-1 V1.6.1, clause 7.1.

Refer to ETSI EN 300 328 V2.1.1,

See Sub-Clause 5.3.2.1 of ETSI EN 300 328 for the test conditions

See Sub-Clause 5.3.2.2.1.1 of ETSI EN 300 328 for conducted method.

### 6.5. Measurement Result: Refer to next page for the details.

### 6.5.1. Test Results:

Example Calculation:

Pburst values (A) = Reading + Cable Loss

RF output power (P) = A+G+Y

Ambient temperature: 25°C

Relative humidity: 60%

Test Date: 2020/09/30

Test Mode: BT LE

Pburst values (value "A" in dBm)

antenna assembly gain "G" in dBi

0.14 dBi

beamforming gain "Y" in dB

0.00 dB

Cable Loss=

21.00 dB

TEST CONDITIONS			TRANSMITTER POWER (dBm)								
			Lowest Frequency			Middle Frequency		Highest Frequency			
Temp -40 °C	Vmin	4.5 V	P	5.84	dBm	P	5.84	dBm	P	5.84	dBm
			A	5.50	dBm	A	5.50	dBm	A	5.50	dBm
			Reading -15.50 dBm			Reading -15.50 dBm		Reading -15.50 dBm			
	Vmax	5.5 V	P	5.84	dBm	P	5.74	dBm	P	5.74	dBm
			A	5.50	dBm	A	5.40	dBm	A	5.40	dBm
			Reading -15.50 dBm			Reading -15.60 dBm		Reading -15.60 dBm			
Temp 25 °C	Vnom	5 V	P	4.74	dBm	P	4.64	dBm	P	4.64	dBm
			A	4.40	dBm	A	4.30	dBm	A	4.30	dBm
			Reading -16.60 dBm			Reading -16.70 dBm		Reading -16.70 dBm			
Temp 80 °C	Vmin	4.5 V	P	4.74	dBm	P	4.64	dBm	P	4.64	dBm
			A	4.40	dBm	A	4.30	dBm	A	4.30	dBm
			Reading -16.60 dBm			Reading -16.70 dBm		Reading -16.70 dBm			
	Vmax	5.5 V	P	4.74	dBm	P	4.64	dBm	P	4.64	dBm
			A	4.40	dBm	A	4.30	dBm	A	4.30	dBm
			Reading -16.60 dBm			Reading -16.70 dBm		Reading -16.70 dBm			
Limit(P)			36dBm								
Measurement uncertainty			+ 0.28dB / - 0.30dB								

## **7 Transmitter Spurious Emissions Measurement**

### **7.1. Limit:**

According to AS/NZS 4268:2017, Section 6.2.2

### **7.2. Measurement Equipment Used:**

Refer to section 6.2 of present report.

### **7.3. Test Setup:**

Refer to section 6.3 of present report.

### **7.4. Test Procedure:**

Refer to ETSI EN 300 440-1 V1.6.1, clause 7.3.

### **7.5. Measurement Result:**

Refer to next page for the details.

### 7.5.1. Test Results: (Radiated)

Ambient temperature: 25 °C      Relative humidity: 60 %      Test Date: 2020/09/30

Test Mode: BLE mode, TX CH Low

No	Freq MHz	Reading dBm	Aux dB	Level dBm	Limit dBm	Margin dB	Pol V/H
1	71.71	-57.95	2.58	-55.37	-54.00	-1.37	VERTICAL
2	554.77	-82.22	9.03	-73.19	-54.00	-19.19	VERTICAL
3	614.91	-84.54	10.73	-73.81	-54.00	-19.81	VERTICAL
4	665.35	-83.17	12.65	-70.52	-54.00	-16.52	VERTICAL
5	741.01	-83.93	13.74	-70.19	-54.00	-16.19	VERTICAL
6	833.16	-84.19	14.39	-69.80	-54.00	-15.80	VERTICAL
7	4804.00	-69.17	15.71	-53.46	-30.00	-23.46	VERTICAL
8	7206.00	-70.00	22.45	-47.55	-30.00	-17.55	VERTICAL
1	95.96	-64.33	0.55	-63.78	-54.00	-9.78	HORIZONTAL
2	527.61	-82.19	9.33	-72.86	-54.00	-18.86	HORIZONTAL
3	562.53	-81.17	10.35	-70.82	-54.00	-16.82	HORIZONTAL
4	640.13	-84.02	11.57	-72.45	-54.00	-18.45	HORIZONTAL
5	751.68	-84.87	14.28	-70.59	-54.00	-16.59	HORIZONTAL
6	792.42	-84.02	14.18	-69.84	-54.00	-15.84	HORIZONTAL
7	4804.00	-66.84	15.63	-51.21	-30.00	-21.21	HORIZONTAL
8	7206.00	-63.67	23.43	-40.24	-30.00	-10.24	HORIZONTAL

Measurement uncertainty	30MHz - 80MHz: 5.04dB
	80MHz -1000MHz: 3.76dB
	1GHz - 26GHz: 4.45dB

Remark:

1. The emission behaviors belong to narrowband spurious emission.
2. Remark " --- " means that the emission level is too low to be measured
3. Aux: Field strength to EIRP correction factor
4. Level (dBm) = Reading (dBm) + Aux (dB)
5. Measurement Range upto 26GHz.

Ambient temperature: 25 °C      Relative humidity: 60 %      Test Date: 2020/09/30

Test Mode: BLE mode, TX CH High

No	Freq MHz	Reading dBm	Aux dB	Level dBm	Limit dBm	Margin dB	Pol V/H
1	71.71	-64.58	2.58	-62.00	-54.00	-8.00	VERTICAL
2	482.02	-83.49	8.98	-74.51	-54.00	-20.51	VERTICAL
3	567.38	-83.27	9.35	-73.92	-54.00	-19.92	VERTICAL
4	656.62	-83.02	12.33	-70.69	-54.00	-16.69	VERTICAL
5	702.21	-83.98	13.87	-70.11	-54.00	-16.11	VERTICAL
6	792.42	-83.79	13.47	-70.32	-54.00	-16.32	VERTICAL
7	4960.00	-71.04	16.40	-54.64	-30.00	-24.64	VERTICAL
8	7440.00	-71.26	23.04	-48.22	-30.00	-18.22	VERTICAL
1	95.96	-64.69	0.55	-64.14	-54.00	-10.14	HORIZONTAL
2	545.07	-80.76	9.89	-70.87	-54.00	-16.87	HORIZONTAL
3	581.93	-80.64	10.81	-69.83	-54.00	-15.83	HORIZONTAL
4	636.25	-83.89	11.54	-72.35	-54.00	-18.35	HORIZONTAL
5	713.85	-83.80	13.03	-70.77	-54.00	-16.77	HORIZONTAL
6	778.84	-84.28	14.21	-70.07	-54.00	-16.07	HORIZONTAL
7	4960.00	-68.51	16.15	-52.36	-30.00	-22.36	HORIZONTAL
8	7440.00	-65.13	23.28	-41.85	-30.00	-11.85	HORIZONTAL

Measurement uncertainty	30MHz - 80MHz: 5.04dB
	80MHz -1000MHz: 3.76dB
	1GHz - 26GHz: 4.45dB

Remark:

1. The emission behaviors belong to narrowband spurious emission.
2. Remark " --- " means that the emission level is too low to be measured
3. Aux: Field strength to EIRP correction factor
4. Level (dBm) = Reading (dBm) + Aux (dB)
5. Measurement Range upto 26GHz.

## 8 Emission Bandwidth Measurement

### 8.1. Limit:

99% power emission bandwidth shall within 2400MHz and 2483.5MHz.

According to AS/NZS 4268:2017, section 6.5.

### 8.2. Measurement Equipment Used:

Refer to section 6.2 of present report.

### 8.3. Test Setup:

Refer to section 6.3 of present report.

### 8.4. Test Procedure:

Refer to section 6.5 of AS/NZS 4268 for the details.

### 8.5. Measurement Result:

Ambient temperature: 25 °C      Relative humidity: 60 %      Test Date: 2020/09/30

Channel	Measured Frequency (MHz)	Limit (MHz)
Upper Frequency	2401.532	>2400
Lower Frequency	2480.616	<2483.5

## **9 Operating Frequencies Measurement**

### **9.1. Limit:**

2400MHz and 2483.5MHz.

According to AS/NZS 4268:2017 section 6.6.

### **9.2. Measurement Equipment Used:**

Refer to section 6.2 of present report.

### **9.3. Test Setup:**

Refer to section 6.3 of present report.

### **9.4. Test Procedure:**

Refer to ETSI EN 300 440-1 V1.6.1, clause 7.2.2 and 7.2.3.

Refer to ETSI EN 300 328 V2.1.1, clause 4.3.2.7



## 9.5. Measurement Result:

### Test Results: BT BLE mode

Ambient temperature: 25 °C

Relative humidity: 60%

Test Date: 2020/09/30

antenna assembly gain "G" in dBi

0.14 dBi

beamforming gain "Y" in dB

0.00 dB

Cable Loss=

1.00 dB

TEST CONDITIONS				FREQUENCY (MHz)	
				Lowest	Highest
Temp -40 °C	V <sub>min</sub>	4.50	V	2402.0013	2480.0013
	V <sub>max</sub>	5.50	V	2402.0012	2480.0015
Temp 25 °C	V <sub>nom</sub>	5.00	V	2402.0014	2480.0013
Temp 80 °C	V <sub>min</sub>	4.50	V	2402.0013	2480.0013
	V <sub>max</sub>	5.50	V	2402.0012	2480.0015
Measured frequencies (lowest and highest)				f <sub>L</sub> = 2402.0012 MHz	f <sub>H</sub> = 2480.0015 MHz
Limit				2400.0000 MHz	2483.5000 MHz
Measurement Uncertainty				+/- 120kHz	

## **10 Receiver Emissions Measurement**

### **10.1. Limit:**

According to section 7.2 of AS/NZS 4268:2017  
25MHz to 1 GHz 2 nW ERP (-57 dBm).  
1GHz to 40 GHz 20 nW ERP (-47 dBm).

### **10.2. Measurement Equipment Used:**

Refer to section 6.2 of present report.

### **10.3. Test Setup:**

Refer to section 6.3 of present report.

### **10.4. Test Procedure:**

Refer to ETSI EN 300 440-1 V1.6.1, clause 8.4.

## 10.5. Measurement Result:

Ambient temperature: 25°C

Relative humidity: 60%

Test Date: 2020/09/30

Test Mode: BLE mode, RX CH Low

No	Freq MHz	Reading dBm	Aux dB	Level dBm	Limit dBm	Margin dB	Pol V/H
1	71.71	-71.43	2.58	-68.85	-57.00	-11.85	VERTICAL
2	106.63	-72.97	0.49	-72.48	-57.00	-15.48	VERTICAL
3	150.28	-83.61	6.17	-77.44	-57.00	-20.44	VERTICAL
4	264.74	-78.62	4.68	-73.94	-57.00	-16.94	VERTICAL
5	670.20	-86.30	12.82	-73.48	-57.00	-16.48	VERTICAL
6	766.23	-84.82	13.62	-71.20	-57.00	-14.20	VERTICAL
7	2932.00	-71.69	7.08	-64.61	-47.00	-17.61	VERTICAL
8	5284.00	-73.08	17.29	-55.79	-47.00	-8.79	VERTICAL
1	71.71	-71.52	3.91	-67.61	-57.00	-10.61	HORIZONTAL
2	106.63	-71.22	1.11	-70.11	-57.00	-13.11	HORIZONTAL
3	252.13	-75.69	4.57	-71.12	-57.00	-14.12	HORIZONTAL
4	561.56	-82.25	10.32	-71.93	-57.00	-14.93	HORIZONTAL
5	719.67	-84.78	13.23	-71.55	-57.00	-14.55	HORIZONTAL
6	903.97	-85.20	15.85	-69.35	-57.00	-12.35	HORIZONTAL
7	3100.00	-71.74	7.82	-63.92	-47.00	-16.92	HORIZONTAL
8	5284.00	-72.31	16.87	-55.44	-47.00	-8.44	HORIZONTAL

Measurement uncertainty	30MHz - 80MHz: 5.04dB
	80MHz -1000MHz: 3.76dB
	1GHz - 26GHz: 4.45dB

### Remark:

1. The emission behaviors belong to narrowband spurious emission.
2. Remark " --- " means that the emission level is too low to be measured
3. Aux: Field strength to EIRP correction factor
4. Level (dBm) = Reading (dBm) + Aux (dB)
5. Measurement Range upto 26GHz.

Ambient temperature: 25°C

Relative humidity: 60%

Test Date: 2020/09/30

Test Mode: BLE mode, RX CH High

No	Freq MHz	Reading dBm	Aux dB	Level dBm	Limit dBm	Margin dB	Pol V/H
1	71.71	-71.41	2.58	-68.83	-57.00	-11.83	VERTICAL
2	106.63	-72.42	0.49	-71.93	-57.00	-14.93	VERTICAL
3	252.13	-76.42	4.85	-71.57	-57.00	-14.57	VERTICAL
4	491.72	-84.95	8.97	-75.98	-57.00	-18.98	VERTICAL
5	537.31	-84.31	8.92	-75.39	-57.00	-18.39	VERTICAL
6	721.61	-85.35	13.81	-71.54	-57.00	-14.54	VERTICAL
7	3352.00	-71.61	8.75	-62.86	-47.00	-15.86	VERTICAL
8	5865.00	-74.22	18.42	-55.80	-47.00	-8.80	VERTICAL
1	95.96	-70.30	0.55	-69.75	-57.00	-12.75	HORIZONTAL
2	180.35	-77.68	2.42	-75.26	-57.00	-18.26	HORIZONTAL
3	252.13	-75.63	4.57	-71.06	-57.00	-14.06	HORIZONTAL
4	431.58	-83.74	7.82	-75.92	-57.00	-18.92	HORIZONTAL
5	558.65	-82.21	10.25	-71.96	-57.00	-14.96	HORIZONTAL
6	747.80	-84.45	14.21	-70.24	-57.00	-13.24	HORIZONTAL
7	2743.00	-70.31	6.81	-63.50	-47.00	-16.50	HORIZONTAL
8	5697.00	-74.43	18.02	-56.41	-47.00	-9.41	HORIZONTAL

Measurement uncertainty	30MHz - 80MHz: 5.04dB
	80MHz -1000MHz: 3.76dB
	1GHz - 26GHz: 4.45dB

Remark:

1. The emission behaviors belong to narrowband spurious emission.
2. Remark " --- " means that the emission level is too low to be measured
3. Aux: Field strength to EIRP correction factor
4. Level (dBm) = Reading (dBm) + Aux (dB)
5. Measurement Range upto 26GHz.

## 11 Radiated Peak Power Spectral Density Measurement

### 11.1. Limit:

According to AS/NZS 4268:2017, Table 1, Note 2.

The radiated peak power spectral density in any 3kHz is limited to 25mW per 3kHz.

### 11.2. Measurement Equipment Used:

Refer to section 6.2.

### 11.3. Test Setup:

Refer to section 6.3.

### 11.4. Test Procedure:



1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5MHz, Sweep=100s, Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

### 11.5. Measurement Result:

Channel	Power Density Reading (dBm)	Antenna Gian (dBi)	PDS e.i.r.p.	Maximum Limit (dBm)
Low	-6.63	0.14	-6.49	13.97
Mid	-7.84	0.14	-7.70	13.97
High	-8.41	0.14	-8.27	13.97

# **Appendix 1**

## **Photographs of Test Setup**




## **Appendix 2**


### **Photographs of EUT**




*EUT 1*




*EUT 2*




***EUT 3***




***EUT 4***



*EUT 5*




*EUT 6*







**EUT 7**



**EUT 8**



***EUT 9***



*~ End of Report ~*